

Representing the latest advancement in Night Vision optics, the ATN PS22 gives your daytime scope Night Vision capability in a matter of seconds.

The ATN PS22 mounts in front of a daytime scope to enable nighttime operation. No shift of impact, no need to rezero nor change of eye relief occurs. The ATN PS22 uses the latest in image intensifier tube technology for outstanding resolution and performance.

Precision optical alignment is essential for a front sight system to work properly. This is why each ATN PS22 is individually tested and aligned on an optical scale by our engineers to provide perfect alignment.

The ATN PS22 is one of the most compact and lightweight NV systems in its class, at only 600 grams.

- Easily changes daytime scope to Night Vision
- Mounts in front of daytime scope, no re-zeroing required
- Multi-coated all-glass optics
- Fast catadioptic front lens system
- Large 21 mm eyepiece/output window
- Lightweight and rugged
- Comes with Quick Release Mount
- Optional 7/8" weaver mount
- Optional Scope Mounting System for coupling to the objective of the day scope (25...62 mm diameter)
- Automatic Brightness Control
- Resistance to severe conditions
- Up to 60 hours of continuous operation with one Lithium battery





- 3 Shipping/Storage Case
- Operator's Manual 5 Remote Control
- Two Lithium Battery CR123A
- Quick Release Mount
- Back Cap
- 11 Light Supressor for the scopes with 42-63 mm lens diameter
- 12 Light Supressor for the scopes with 30-42 mm lens diameter
- 13 Light Supressor for Trijicon ACOG scopes

Export Warning: These products are subject to one or more of the export control laws and regulations of the U.S. Government. Pending the model these products are under the control jurisdiction of either the US Department of State or the US Bureau of Industry and Security US Department of Commerce. Export without proper licensing or consent is strictly prohibited.

DAY/NIGHT SYSTEM



PLATFORM RING WITH PICATINNY RAIL

IR Illuminator can be mounted not only onto PS-22 with Picatinny Rail Adapter but also onto a daytime scope using optional an Platform Ring



MOUNTING WITH RUBBER LIGHT SUPPRESSOR

Prevents visible back glow that could give away user's position



SCOPE MOUNTING SYSTEM

Optional Scope Mounting System allows to mount unit onto the objective of a day scope with 25...62 mm diameter



PICATINNY/WEAVER MOUNT

The PS22 is adaptable to almost any weapon which will accept a MIL-STD-1913 (Picatinny) or Weaver rail

SPECIFICATIONS

Magnification	1x
Lens System	F1.44, 80mm
Proshield Lens Coating	Yes
FOV	13°
Exit Pupil	21 mm
Range of Focus	10 m to infinity
Controls	Direct
Remote Control	Yes
Automatic Brightness Control	Yes
Infrared Illuminator	Detachable IR450
IR Indicator	Yes
Power Supply	1 x 3 V CR123A type battery
Battery Life	50 hrs
Environmental Rating	Waterproof
MIL-STD-810	Yes
Operating Temperature	-40 to +50 °C
Storage Temperature	-50 to +70 °C
Dimensions	150x80x72 mm / 5.9x3.2x2,8"
Weight	0.64 kg / 1.4 lbs
Warranty	2 years

TUBE SPECIFICATIONS

HIGH QUALITY 3 GEN IMAGE INTENSIFIER TUBE		
DESCRIPTION	Standard	
GENERATION	3	
PHOTOCATHODE TYPE	GaAs	
RESOLUTION, Ip/mm*	64	
SIGNAL TO NOISE RATIO*	22 Typical	
FIGURE OF MERIT	1600 Typical	
MTTF - MEAN TIME BEFORE FAILURE, hours	10,000	
EXPORT	N/A for Export	

^{*} Specifications are provided for informational purposes only. Actual values may vary

OPTIONAL ACCESSORY

ACDNPS22SM01	Scope Mounting System #1 (25.4; 30mm)
ACDNPS22SM02	Scope Mounting System #2 (38; 42mm)
ACDNPS22SM03	Scope Mounting System #3 (42; 46.7; 48; 48.7-49; 49.5; 50mm)
ACDNPS22SM04	Scope Mounting System #4 (56; 57; 58.7mm)
ACDNPS22SM05	Scope Mounting System #6 (62mm)
ACDNPS22MWVR	7/8" Weaver Mount
ACDNPS22LSR	Day Scope Light Suppresor
ACWSRTRA	Platform Ring

