



SPECIFICATION

TIKKA T3 SPORTER



RIFLE	TIKKA T3	
MODEL	SPORTER	
MANUFACTURER	SAKO Ltd. FINLAND	
OPERATION	TIKKA T3 RH MANUALLY OPERATED BOLT ACTION	
CALIBER	222 REM, 223 REM, 6.5x55 SE, 260 REM, 308 WIN	
OVERALL WEIGHT WITHOUT ACCESSORIES	20", (510 mm) BARREL 9.0 lbs (4.1 kg) 24", (600 mm) BARREL 9.7 lbs (4.4 kg)	
OVERALL LENGTH	20", (510 mm) BARREL 41.3 " (1050 mm) 24", (600 mm) BARREL 44.9 " (1140 mm)	
STEELPARTS	MATTE BLACK	
SIGHTS	DELIVERY WITHOUT SIGHTS RECEIVER EQUIPPED WITH 0.7" (17 mm) SCOPE RAIL AND THREADS FOR THE WEAVER TYPE SCOPE RAIL	
STOCK	MATERIAL	LAMINATED WOOD, OILED
	CHEEK PIECE	HEIGHT ADJUSTMENT 0-1" (0-25 mm) HORIZONTAL ADJUSTMENT 0-0.2" (0-5 mm)
	LENGTH OF PULL	13.2" (335 mm) WITHOUT BUTT SPACER
	BUTT PLATE	ADJUSTABLE BUTT PLATE SYSTEM
	SWIVEL STUDS	EQUIPPED WITH RAIL SLING SWIVEL AND BASIC REAR STOCK SWIVEL
	COLOR	ORANGE/GREY
BARREL	LENGTH	20", (510 mm), MUZZLE THREAD INCLUDED 24", (600 mm), MUZZLE THREAD IS OPTIONAL
	RATE OF TWIST	222 REM 14" 223 REM 8" 223 REM 12" 6.5x55 SE 8" 260 REM 8" 308 WIN 11"
	MUZZLE THREAD	M 18x1, LENGTH 0.6" (16 mm)
TRIGGER MECHANISM	SINGLE STAGE, ADJUSTABLE WEIGHT OF PULL 2-4 lbs (1-2 kg) SINGLE SET TRIGGER MECHANISM IS OPTIONAL 2 STAGE SAFETY LOCKS TRIGGER AND BOLT WHEN ENGAGED	
MAGAZINE	STRUCTURE	DETACHABLE MAGAZINE (2PCS/RIFLE)
	CAPACITY	222 REM.....6 CARTRIDGES 223 REM.....6 CARTRIDGES 6.5x55 SE.....5 CARTRIDGES 260 REM5 CARTRIDGES 308 WIN.....5 CARTRIDGES
	MATERIAL	COMPOSITE
TOOLS	T25 TORX KEY, 0.15" (4 mm) AND 0.2" (5 mm) ALLEN KEYS	