

Standard Features

Rifle Scope Ergonomics
Turret Knob Controls
60hz Super Fast Image
Mil. Spec Construction
Clip-On Capability
Polarity and Zoom Modes
640x480 Thermal Sensor
12 MICRON Technology
100% Made in USA
3 Year Warranty




EXPORT WARNING

Export of the commodities described herein is strictly prohibited without a valid export license issued by the U.S. Department of State, Directorate of Defense Trade Controls as proscribed in the International Traffic in Arms Regulations (ITAR), Title 22 Code of Federal Regulation, Parts 120-130

The IR HUNTERTM MK III takes all the features and performance of the Mark II and adds a long range 7° degree field-of-view lens with a stadiametric range finder. The 4.5x magnification combined with the 640x480 resolution 12um micron LWIR thermal core delivers the perfect combination for a 24/7 weapon sighting platform. One of the benefits of the 12um micron technology is that is delivers 50% more magnification from the same lens used on a 17um micron thermal core, this means our 60mm thermal lens offers the same magnification and FOV of a 90mm lens. We also have 60hz fast frame rate in every MK III system at no addition cost to you. The fast frame rate will be very useful for leading a shot of a fast moving target.

The MARK III brings several new features such as multiple reticle save locations so you can mount the sight on different weapons and keep your reticle position. It has a new digital read-out on the reticle adjustment screen giving you information on exactly how many clicks you have adjusted the system. We also have added two new reticle patterns so you can find the best fit for your application. And to finish off the MARK III we have added a flip-up lens cap, dual lever LT100 LaRue mount, battery extender and a video/download cable to every MKIII thermal weapon sight.



SPECIFICATIONS

Sensor Type Uncooled VOx (Vanadium Oxide)

Thermal Sensitivity

Sensor Resolution

Sensor Pitch

Frame Rate

60hz with a 30hz Power Save Mode

Spectral Responce

Display Type

Display Resolution 640x480 Pixels

Basic Features E-Zoom, Polarity

Advanced Features

DCE - Digital Contrast Enhancment ETR - Enhanced Target Recognition RANGE FINDER - Stadiametric

Start Up Time >4 Seconds

Video Output Analog RS-170 (with Optional Cable)

Battery Type 2 each CR123 3 volt

Battery Life 3.5 Hours @ 60hz 5 Hours @ 30hz

Weapon Mount LaRue Tactical Rail Mount

Reticle Simple and Complex Reticles MOA Adjustments Digital Read-Outs 4 Save Locations

Weight 4.5x Model 1050 grams 2.5x Model 990 grams

2.5x Model 990 grams

Dimensions

4.5x Model 7.6" L x 3.1" H x 3.3" W 2.5x Model 7.4" L x 2.9" H x 3.1" W

Diopter -6 / +4

Eye Relief 27 mm

Environmental

-40c to +55c Operating -45c to +75c Storage




IR DEFENSE CORPORATION

Thermal Systems
2945 Bell Road, Suite 201
Auburn, CA 95603
TOLL FREE: 855-IRHUNTER
530.889.2159 phone / 530.210.2778 fax
info@irdefense.com
www.irdefense.com
www.irhunter.com



IR HUNTER MK III Models					
Model	Sensor	Optical Mag	Digital Mag	Lens	Base FOV
IRHM3-640-60K	640x480	4.5x	36x	60mm f/1.25	7°
IRHM3-640-35K	640×480	2.5x	20x	35mm f/1.2	12°



Actual images taken through the IR HUNTER MKII and MK III at night

MK III STANDARD KIT CONTENTS:

 IR HUNTER MKIII Weapon Sight Part No. IRHM3-xxx-xx

2. LaRue Tactical LT100 Mount Part No. IRDMNT-LT10

3. Shuttered Eyeguard Part No. IRDTWS-3207

4. Tactical Soft Case, Black Part No. IRDTWS-9923

 Operator's Manual Part No. IRDTWS-9925

 QRG Quick Reference Guide Part No. IRDTWS-9926

7. (2) CR123A Lithium Battery Part No. IRDPRT-9123

 Download / Video Cable Part No. IRDACC-9704

9. Battery Extender Part No. IRDACC-6180

IR HUNTER STANDARD KIT



