



SPECIFICATION

TIKKA T3 LITE



TIKKA T3 LITE based on a two locking lug T3 action. Bolt features springloaded plunger ejector and it can be easily stripped down for maintenance. Bolt is made of stainless steel.

The single-column detachable clip MAGAZINE holds 3-4 cartridges. Single-column 4-6-shot (depending on caliber) magazine is available as accessory (not in Short Mag calibers).

The single-stage TRIGGER pull is adjustable from 1 kg to 2 kg (2 to 4 lbs). Safety is two stage type and locks the trigger and the bolt handle when engaged. All models are available with a single-set trigger as option.

The STOCK is made of glass-fiber reinforced copolymer polypropylene and has a buttplate system where the length of pull is adjustable by means of spacers. Straight stock features ambidextrous palm swell.

TIKKA T3 LITE is supplied without OPEN SIGHTS. Optionally available also with open sights with post bead where the rear sight is adjustable sideways and front sight in elevation. Integral rails for the scope mounts are on the top of the receiver. Receiver is also tapped to receive standard (Weaver) scope mount bases.

The free-floating BARREL is cold hammer-forged. Non Magnum models available also with short barrel with thread (calibers 338 Federal, 8x57IS and 9.3x62 M15x1, other calibers M14x1) at the muzzle for muzzle brake or suppressor assembling.

TECHNICAL DATA

Action	caliber	rate of twist	Overall length	
T3	204 Ruger	12"	T3	1080 mm (42 1/2")
	222 Rem	14"	T3 MT	1020 mm (40 3/16")
	223 Rem	8"	T3 Mag	1130 mm (44 1/2")
	223 Rem	12"	Barrel length	
	22-250 Rem	14"	T3	570 mm (22 7/16")
	243 Win	10"	T3 MT	510 mm (20")
	260 Rem	8"	T3 Mag	620 mm (24 3/8")
	7mm-08 Rem	9.5"	Weight	
	308 Win	11"	T3	2.8 kg (6 3/16 lbs)
	338 Federal	10"	T3 MT	2.7 kg (6 lbs)
	25-06 Rem	10"	T3 Mag	2.9 kg (6 3/8 lbs)
	6.5x55 SE	8"	Cartridge capacity	
	270 Win	10"	T3 204 Ruger, 222 Rem, 223 Rem	5 rounds (1 in chamber, 4 in clip magazine)
	7x64	10"	T3 other calibers	4 rounds (1 in chamber, 3 in clip magazine)
	30-06 Sprg	11"		
	8x57IS	9.5"		
	9.3x62	14"		
	7 mm Rem Mag	9.5"		
	300 Win Mag	11"		
	338 Win Mag	10"		
	270 Win Short Mag	10"		
	300 Win Short Mag	11"		