

sako SPECIFICATION sako

SAKO TRG FOLDING STOCK



SAKO TRG FOLDING STOCK based on a series of actions which designated: Short action TRG-22 and Long action TRG-42.

ACTION

Receiver is made by coldhammering method. Three locking lugs makes 60° bolt lift angle possible. The receiver is stabilized with three fastening screws. Finishing is manganese phosphatizing. The bolt is black matte in all models.

MAGAZINE

The magazine is a detachable reliable center fed box magazine. Plugs for easy removing at the rear corners.

TRIGGER

The double-stage trigger pull is adjustable from 2 to 5 lbs. It is also adjustable in length and horizontal or vertical pitch. The entire trigger assembly, including the trigger guard, can be removed from the rifle without disassembling any other part of the rifle.

The safety catch, which is silent in operation, is located inside of the trigger guard. The safety locks the trigger mechanism and locks the bolt in a closed position with the firing pin blocked.

STOCK

The base of the stock is made of aluminium, to which the polyurethane forestock is attached. The stock is hinged behind the pistol grip and folds to the left side and locks into position. Steel parts of the stock are manganese phosphatized and polyurethane parts are painted green or Desert Tan color. Cheek piece is adjustable for height, adjustability range 25 mm, indexing of 5 mm. Rear support is adjustable for height in 54 mm range, coarsely indexed by 6 mm with continuous fine adjustment of 5 mm for each step. Buttplate is adjustable for length of pull in 42 mm range by 6 mm steps and for height in 32 mm range. Pistol grip body has steel loop for hook type military sling swivel. The folding stock is ambidextrous.

BARREL

The free-floating BARREL is cold-hammerforged. TRG-22 available with 20" barrel. Optional detachable muzzle brake can be fitted, which also acts as an efficient flash-hider.

SIGHTS

Sako TRG FOLDING STOCK is supplied without open sights with Picatinny rail mounted for scope mounts mounting. Phosphatized barrel is equipped with groove for emergency sight assembling.

SAKO TRG sharpshooting system optional accessories for special purposes like: Suppressor (for cal. 308 Win), foldable bipod, auxiliary steel peep sights for emergency use, match sight mounting set, night-sight adapter, different slings and swivels, cleaning sets, transit cases etc.

TECHNICAL DATA

Action	caliber	rate of twist	Overall length without muzzle brake	
TRG-22	308 Win	11"	TRG-22 20" barrel	1000 mm (39 3/8")
TRG-42	300 Win Mag	11"	TRG-22 26" barrel	1150 mm (45 1/4")
TRG-42	338 Lapua Mag	12"	TRG-42	1200 mm (47 1/4")
Magazine			Overall length folded without muzzle brake	
TRG-22 308 Win 10-round detachable magazine			TRG-22 20" barrel	750 mm (29 1/2")
TRG-42 300 Win Mag 7-round detachable magazine			TRG-22 26" barrel	900 mm (35 1/2")
TRG-42 338 Lapua Mag 5-round detach. magazine			TRG-42	950 mm (37 3/8")
Max cartridge length			Barrel length	
TRG-22	75 mm (3")		TRG-22 20"	510 mm (20")
TRG-42	95 mm (3 3/4")		TRG-22 26"	660 mm (26")
			TRG-42	690 mm (27 1/8")
Weight				
TRG-22 20" barrel	5.2 kg (11 1/2 lbs)			
TRG-22 26" barrel	5.4 kg (12 lbs)			
TRG-42	5.8 kg (12 3/4 lbs)			