



SPECIFICATION

TIKKA T3 TAC



TIKKA T3 TAC based on a two locking lug T3 action. Bolt features springloaded plunger ejector and it can be easily stripped down for maintenance. Bolt is made of stainless steel and tefloncoated. Other outer steel parts are manganese phosphatized.

The single-column detachable clip MAGAZINE holds 4-6 cartridges. Single-column 3-4-shot (depending on caliber) magazine is available as accessory .

The single-stage TRIGGER pull is adjustable from 1 kg to 2 kg (2 to 4 lbs). Safety is two stage type and locks the trigger and the bolt handle when engaged. All models are available with a single-set trigger as option.

The STOCK is made of glass-fiber reinforced copolymer polypropylene and has a buttplate system where the length of pull is adjustable by means of spacers. Height adjustable cheek piece and extra-wide forend carried out with add-ons. Straight stock features ambidextrous palm swell. Adjustable cheek piece can also be used by lefthanded shooter. Standard sling swivel studs under the forend and butt stock as standard. Military type sling swivel studs can be optionally attached in both sides of the butt stock and forend and under the butt stock and forend.

TIKKA T3 TAC is supplied without OPEN SIGHTS. Optionally available also with open sights with post bead where the rear sight is adjustable sideways and the front sight in elevation. Picatinny rail for the scope mounts is on the top of the receiver.

The heavy, free-floating BARREL is cold hammer-forged and supplied with muzzle thread for muzzle brake or suppressor assembly. Available two barrel lengths.

TECHNICAL DATA

Action	caliber	rate of twist	Overall length	
T3	223 Rem	8"	T3 24" barrel	1110 mm (43 3/4")
	308 Win	11"	T3 20" barrel	1020 mm (40 5/32")
	300 Win Mag	11"	Barrel length	
Cartridge capacity			T3 24"	600 mm (23 3/4")
T3 223 Rem 7 rounds (1 in chamber, 6 in clip magazine)			T3 20"	510 mm (20")
T3 Mag. calibers 5 rounds (1 in chamber, 4 in clip mag.)			Weight	
T3 other calibers 6 rounds (1 in chamber, 5 in clip mag.)			T3 24" barrel	3.7 kg (8 5/32 lbs)
			T3 20" barrel	3.6 kg (8 lbs)